

Polyco Maxima 30cm Heavy Duty Flock Lined Natural Rubber Glove



PRODUCT INFORMATION

ltem Number	51
Product Colour	Black
Size Range	6,7,9,10
Primary Coating Polymer	Latex
Grip	Slip-Resistant
Lining	Cotton Flock

FEATURES

Chemical Resistant: Achieves type A chemical resistance according to EN ISO 374-1, for protection against at least 6 different chemicals

Grip: Slip-resistant pattern on the palm enhances grip

Lining: Flock lining eases donning and removal and absorbs perspiration keeping the hands cool and comfortable

Length: 30cm

Primary Coating Polymer: Latex

Virus/Non Virus Standard: Conforms with the requirements of EN ISO 374-5, for protection against bacteria & fungi

Fit: Designed to be close fitting to give maximum dexterity for the most tactile of operations

Chemical Resistant: Provides protection against a wide range of chemicals and cleaning agents

Abrasion Resistant: Achieves Level 2 for abrasion resistance as defined by European Standard EN 388

SECTORS

Construction & Utility • Food Manufacturing and Preparation • Janitorial • Waste Management and Local authority



STANDARDS













0598

2020X

AKLMN PST

CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.

Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

PACKING

12 pairs per polybag 48 pairs per case 60 cases per pallet

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555





DISPOSAL INSTRUCTIONS

Dispose of responsibly and in line with local guidance.

INNER PACKAGING



OUTER PACKAGING



Size	Outer Packaging Barcode
6	05010699806925
7	05010699806932
9	05010699806949
10	05010699806956

 $For further technical information, please contact Customer Services on 0333\,320\,8550\, or the \, Technical \, team \, on \, 0333\,320\,8555\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, the \, Technical \, team \, on \, t$