

Polyco Duo Plus™ 60 Double Dipped Latex Flock Lined Glove (0.6mm, 33cm)



### **PRODUCT INFORMATION**

ltem Number	RU560
Product Colour	Blue
Size Range	7-10
Primary Coating Polymer	Latex
Grip	Slip-Resistant
Lining	Cotton Flock

#### **FEATURES**

**Chemical Resistant:** Achieves type A chemical resistance according to EN ISO 374-1, for protection against at least 6 different chemicals

Provides protection against a wide range of chemicals and cleaning agents

Grip: Slip-resistant pattern on the palm enhances grip

Length: 33cm

**Primary Coating Polymer: Latex** 

Virus/Non Virus Standard: Conforms with the requirements of EN ISO 374-5, for protection against bacteria & fungi

**Abrasion Resistant:** Achieves Level 1 for abrasion resistance as defined by European Standard EN 388

#### **SECTORS**

Food Manufacturing and Preparation • Janitorial • Waste Management and Local authority

#### **STANDARDS**

Tested in compliance with Commission Regulation (EU) No 10/2011 for Food contact















1010X

AKLMN PST





### **STANDARDS**



## CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.

Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

## **STORAGE INSTRUCTIONS**

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

# **PACKING**

12 pairs per polybag 48 pairs per case 100 cases per pallet

### **DISPOSAL INSTRUCTIONS**

Dispose of responsibly and in line with local guidance.

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555



Polyco Duo Plus™ 60 Double Dipped Latex Flock Lined Glove (0.6mm, 33cm)



# **INNER PACKAGING**



# **OUTER PACKAGING**



Size	Outer Packaging Barcode
7	05010699820044
8	05010699820051
9	05010699820068
10	05010699820075

 $For further technical information, please contact Customer Services on 0333\,320\,8550\, or the \, Technical \, team \, on \, 0333\,320\,8555\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, the \, Technical \, team \, on$