

Chemprotec® Heavyweight 44cm Unlined Natural Rubber



PRODUCT INFORMATION

ltem Number	SC105
Product Colour	Black
Size Range	9-10
Primary Coating Polymer	Latex
Grip	Chlorinated
Lining	Unlined

FEATURES

Length: Available in various lengths providing protection to the top of the arm

Abrasion Resistant: Achieves maximum score for abrasion resistance as defined by European Standard EN388

Chemical Resistant: Achieves type A chemical resistance according to EN ISO 374-1, for protection against at least 6 different chemicals

Length: 40cm

Closure: Beaded cuff for additional strength and prevention of liquid roll back

Fit: Treated to harden the surface of the glove leaving it smooth to the touch

Heat Resistant: Heat resistant to contact heat level 1 to broaden real world application suitability

Primary Coating Polymer: Latex

Virus/Non Virus Standard: Conforms with the requirements of EN ISO 374-5, for protection against bacteria & fungi

Lining: Unlined for easy donning; and also allows for an under glove to be worn for added comfort

Chemical Resistant: Provides protection against a wide range of chemicals and cleaning agents

SECTORS

Construction & Utility • Janitorial • Waste Management and Local authority



STANDARDS













0598

4121X

AKLMI OPT

Х1ХХХХ



CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.

Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555



Chemprotec® Heavyweight 44cm Unlined Natural Rubber



DISPOSAL INSTRUCTIONS

Dispose of responsibly and in line with local guidance.

Size	Outer Packaging Barcode
9	05010699817358
10	05010699817365

PACKING

1 pair per polybag 15 pairs per case 50 cases per pallet

 $For further technical information, please contact Customer Services on 0333\,320\,8550\, or the \, Technical \, team \, on \, 0333\,320\,8555\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\,320\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical \, team \, on \, 0333\, or \, the \, Technical$