

## PRODUCT INFORMATION

Item Number	7552
Product Colour	Yellow
Size Range	22 inch
Primary Coating Polymer	Uncoated
Grip	Uncoated
Cut Score	C
Heat Resistance	Contact Heat Level 2

## FEATURES

**Heat Resistant:** Achieves Level 2 for Contact Heat according to EN 407. Can withstand temperatures of 250°C  
100% Kevlar® aramid fibre offers increased resistance to heat

**Cut Resistant:** Achieves cut level C according to EN388, for protection in high risk cut hazard applications.

**Cut Resistant:** Kevlar® provides increased protection against cuts, slashes and abrasion, while maintaining a high degree of dexterity for the wearer

**Unique Feature:** Machine washable to extend life

**Abrasion Resistant:** Achieves Level 2 for abrasion resistance as defined by European Standard EN 388

## SECTORS

Automotive • Construction & Utility • Engineering and Manufacturing • Warehousing, Transport and Logistics

## STANDARDS



PPE CAT II



2X4XC



X2XXXX



## CAUTION

May contain latex in elasticated cuff which can cause allergic reactions, including anaphylactic response.

## STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

## DISPOSAL INSTRUCTIONS

Dispose of responsibly and in line with local guidance.

## PACKING

24 sleeves per polybag  
96 sleeves per case  
30 cases per pallet

## OUTER PACKAGING BARCODE

05010699809117

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555