



**PRODUCT INFORMATION**

<b>Item Number</b>	AFG41-0
<b>Size Range</b>	6-12
<b>Primary Coating Polymer</b>	Latex
<b>Max Working AC Voltage</b>	1000.00 V

**FEATURES**

**Electrical Handling:** Class 0, for a maximum working AC voltage of 1000V  
**Arc flash Class 2** according to EN 61482-1-2, with an ATPV of 71.6 cal/cm2  
**Electrical Insulating glove 3 in 1:** dielectric, mechanical and arc flash protection

**Length:** 41cm length for extended protection up the arm

**Electrical Handling:** Internal black/external red to make visual inspection easier  
 Each pair of gloves is supplied with a pair of cotton fingerless under gloves for improved comfort  
 Unique formulation of the rubber compound makes gloves extremely flexible

**Chemical Resistant:** Passes special properties 'RC' for protection against acid, oil, ozone and extremely low temps

**SECTORS**

Automotive • Engineering and Manufacturing • Oil, Gas & Renewables • Warehousing, Transport and Logistics

**STANDARDS**



**CAUTION**

Contains latex which may cause allergic reactions, including anaphylactic response.  
 Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

**STORAGE INSTRUCTIONS**

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

**DISPOSAL INSTRUCTIONS**

Dispose of responsibly and in line with local guidance.

Reusable Gloves

Electrical Handling

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

Size	Outer Packaging Barcode
6	N/A
7	N/A
8	N/A
9	N/A
10	N/A
11	N/A
12	N/A

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555